

DX12

Dynaproofed outback rugged canvas



















PRODUCT SPECIFICATIONS

DX12 is a medium weight, general-purpose blended poly/cotton canvas which is especially suitable for a wide range of applications. These include: swags, marquee and tepee roofs and walls, temporary shelters, under tarpaulins, box-trailer covers and heavy-duty campervan roofs and walls. DX12 is also perfect for annexe roofs in semi-permanent situations, as well as high quality family marquee roofs and walls.

Weight:	Dynaproofed: 505g/sq.m (14.9 oz) +/- 30gsm
Width:	Dynaproofed: 204cm
Construction:	Woven 52/48 Poly/Cotton Plain Weave. 22.8 ends per cm. 15 picks per cm. Yarn Count 2/12 ECC x 2/12 ECC.
Maximum Shrinkage:	2.5% in Warp
Tear Resistance: (AS 2001.2.10)	WARP – 116N WEFT – 68N
Breaking Force: (AS 2001.2.3)	WARP – 2195N WEFT – 1523N
Hydrostatic Head: (AS 2001.2.17)	800mm min
Cone Test: (AS 2001.2.18)	Pass

Stock Colours:

 Brunswick Green	 Antelope	 Blue	 Maroon
 Grey	 Olive	 Khaki	 Green
 Lt. Grey	 Black	 Navy	 Aus Cam D.P.
 Beige	 Lt. Sand	 Dark Green	 Olive F/R*

*Flammability: Olive F/R tested to AS1530 Part 3 Results available on request



Contender NZ Ltd
3/19 Hannigan Drive, Panmure
contender@contender.co.nz
P 09 527 2123 F 09 527 1935
www.contender.co.nz